



## VLMT.EX15524 Special System Water Control Valves, Pressure-reducing and Pressure-control Type

[Page Bottom](#)

### Special System Water Control Valves, Pressure-reducing and Pressure-control Type

[See General Information for Special System Water Control Valves, Pressure-reducing and Pressure-control Type](#)

#### Z-TIDE VALVES INDUSTRIAL CO LTD

EX15524

41 Sec 2 New Taipei Blvd  
Sanchong District  
New Taipei, 241 TAIWAN

**Pilot-operated pressure-control valve**, Model UL-BFR, in ductile iron body, consisting of the following sizes and pressures:

Model	Body Type	Size, NPS	Max Rated Inlet Pressure (psig)	Outlet Pressure Setting Range (psig)
UL-BFR	Globe	3, 4, 6 and 8	300	30-100

Class 150 flanges are intended to be installed on systems not exceeding 250 psig.

The manufacturer's design and installation instructions, dated 04/28/14, include a description of the performance characteristics for both flow and static conditions.

[Last Updated](#) on 2015-12-17

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2016 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2016 UL LLC".